NSR - 08 P 2 - 32 F 1 - 18.0 - HT

Or L01

Series Designation
NSR = Nano Strip

Connector Size
Number of Contacts (40 Max)

Shell Style
P = Pin Contact
S = Socket Contact

Hardware
0 - None
1 - One Guide Pin (Socket Side) One Hole (Pin Side)
2 - Two Guide Pins (Socket Side) Two Holes (Pin Side)

Temp Range
Blank = 125°C*
HT = 200°C (Special Order)

Wire Length
18.0 = 18" *
36.0 = 36" *
Other lengths available by specifying in inches XX.X" or cm (e.g. M46)

Wire Color
1 = All White*
2 = All Yellow
3 = Pure Tin Solid Wire (RoHS)
4 = Gold Plated Solid Wire (RoHS)
6 = Solid Colors Repeat/No Stripes*
7 = Tin Plated Solid Wire (60/40)
Other Color = Please Consult Factory

Wire Type
C = Solid Copper (Uninsulated) per QQ-W-343
F = Type 'ET' Teflon per Nema HP3 (Type 6)*
Y = Tefzel per MIL-W-22759/33 (30 AWG Only)
X = per DSCC 04047-30A (White Only) (30 AWG Only)
T = Flat Tail
Other Type = Please Consult Factory

Wire Size (AWG)
30, 32*, 34, 36 AWG

Circuit Termination: (Replaces all of Above)
-L01, -L03, -L05, -L06

* - Indicates Preferred Standard
Please consult factory for more Information