



















WIRED CONNECTOR

- Low Profile Metal Shell Connector w/Wire Leads
- Environmentally Sealed
- Operating Temperature -50° C to 200° C
- 9 to 51 Contacts




HOW TO ORDER

* Indicates preferred standard, ** Consult factory for other plating options , *** Leave blank if no Mounting Option is required



AP	R	51-3	P	Ø2 -	26	E	6 -	18.0 -	SØ1		
Series	Insulator	Contacts	Contact Gender	Hardware	Wire Gauge**	Wire Type**	Color Code	Length**	Finish**	Temp Range	Mounting Option***
A = Metal Shell (Receptacle)	R = PPS	Ø9	P=Male/Pin (Plug Side)	Ø No Hardware	24	C = Solid Wire, Uninsulated	1 = White	*18.0	Blank= Cadmium	*Blank =125C	F01-Float Mount
		15			25		2 = Yellow	*36.0		HT = 200C	
AP = Metal Shell w/ Plastic shroud (Plug)		21	S=Female/Socket (Receptacle Side)	*Ø2 22 (Swaged) Allen Head Jackscrew	26*	*E = Stranded w/Teflon Insulation, per NEMA HP3-EX	3 = Tin Plated (Solid Wire)		*SØ1= Nickel		
		25			28		4 = Gold Plated (Solid Wire)				
		31		Ø3 High Profile Allen Head Jackscrew	3Ø	F = Stranded, w/Teflon Insulation, per NEMA HP3-ET	5 = Color Code per MIL-STD-681 (Non-Repeating Colors)		SØ3 = Black Anodize		
		37					*6 = 1Ø Solid Colors, Repeating				
				*Ø5 Slotted Head Jackscrew		M = Stranded, w/Teflon Insulation, per SAE-AS22759/11		SØ6 = Olive-Drab Cadmium			
		51-3					Y = Stranded w/Tefzel Insulation, per SAE-AS22759/33				
				Ø6 High Profile Slotted Head Jackscrew				SØ7 = Titanium			
											
		Ø7 Jack post				SØ9 = Stainless					
											

DIMENSIONS



RECEPTACLE (SOCKETS)

PLUG (PINS)



Size	ALL		A/AP SERIES								
	A Max.	B Max.	C Max.	D Max.	E Max.	H Max.	G Max.	J Max. (Skt)	K Max. (Pin)	L Max. (Skt)	M Max. (Pin)
9	.785 (19.94)	.376 (9.55)	.393 (9.98)	.565 (14.35)	.218 (5.54)	.218 (5.54)	.174 (4.42)	.182 (4.62)	.209 (5.31)	.375 (9.57)	.395 (10.03)
15	.935 (23.75)	.526 (13.36)	.543 (13.79)	.715 (18.16)	.218 (5.54)	.218 (5.54)	.174 (4.42)	.182 (4.62)	.209 (5.31)	.375 (9.57)	.395 (10.03)
21	1.085 (27.56)	.693 (17.17)	.693 (17.60)	.865 (21.97)	.218 (5.54)	.218 (5.54)	.174 (4.42)	.182 (4.62)	.209 (5.31)	.375 (9.57)	.395 (10.03)
25	1.185 (30.10)	.776 (19.71)	.793 (20.14)	.965 (24.51)	.218 (5.54)	.218 (5.54)	.174 (4.42)	.182 (4.62)	.209 (5.31)	.375 (9.57)	.395 (10.03)
31	1.335 (33.91)	.926 (23.52)	.943 (23.95)	1.115 (28.32)	.218 (5.54)	.218 (5.54)	.174 (4.42)	.182 (4.62)	.209 (5.31)	.375 (9.57)	.395 (10.03)
37	1.485 (37.72)	1.076 (27.33)	1.093 (27.76)	1.265 (32.13)	.218 (5.54)	.218 (5.54)	.174 (4.42)	.182 (4.62)	.209 (5.31)	.375 (9.57)	.395 (10.03)
51-3	1.435 (36.45)	1.026 (26.06)	1.041 (26.44)	1.215 (30.86)	.254 (6.45)	.254 (6.45)	.223 (5.66)	.182 (4.62)	.209 (5.31)	.375 (9.57)	.395 (10.03)

MICRO-D WIRED SERIES METAL PERFORMANCE DATA, MATERIALS AND FINISHES

PERFORMANCE DATA

10-E	ELECTRICAL
CONTACT RESISTANCE:	8 m Ω max.@ 2.5 A
CURRENT RATING (SIGNAL CONTACTS):	3 A max.
DIELECTRIC WITHSTANDING VOLTAGE:	900 VAC at sea level, 300 VAC at 70,000 ft.
INSULATION RESISTANCE:	5,000 M Ω min.

10-M	MECHANICAL
CONTACT ENGAGING FORCE:	6 oz max. (Contact average is 3 oz.)
CONTACT SEPARATING FORCE:	0.5 oz. min.
CONNECTOR MATING FORCE:	10 oz. x number of contacts max.
CONNECTOR UNMATING FORCE:	10 oz. x number of contacts min.
VIBRATION:	No damage or interruption detected (one microsecond sensitivity) EIA-364-28 Condition IV
SHOCK:	No damage or interruption detected (one microsecond sensitivity) EIA-364-27 Condition E
DURABILITY:	No mechanical or electrical defects after 500 matings.
SALT SPRAY:	No exposure of base metal or loss of performance after 96 hours for both Nickel and Cadmium plating

MATERIALS AND FINISHES

10-M&F	MATERIALS AND FINISHES
Pin Contacts	Beryllium Copper (C17200) per ASTM B194.
Socket Contacts	Copper alloy (C21000) per ASTM B36
Contact Plating	Gold plated per ASTM-B488. 50 microinches min. is the standard thickness.
Metal Shells	Aluminum alloy per SAE-AMS-QQ-A-200/8, type 6061-T6. Finish is cadmium per SAE-AMS-QQ-P-416,TYPE II, CLASS 3, with suitable underplate with yellow chromate, this plating is not RoHS compliant. Or Finish Electroless Nickel plate per SAE AMS2404, class 3 or 4, .0005 minimum thickness. (RoHS compliant). For other finishes detail consult factory.
Insulator Material Shell	Polyphenylene sulfide (PPS) per MIL-M-24519 GST 40F or ASTM D5927. Color Black.
Interfacial Seals	Fluorosilicone elastomer per MIL-R-25988. Standard on "M" Series socket face.
Hardware	Corrosion resistant steel per ASTM A 582/A582 or ASTM A 581/A581M, Passivated per SAE AMS-2700
O-Ring For Front & Rear Panel Series	Non Conductive: Fluorosilicone or Silicone Conductive: Conductive Fluorosilicone