


PART DWG	DATE	ECN NO.	APPD BY	REL BY
REV ISSUE	05/13/19	UMI7146	T.POMBAERT	PER



3. PERFORMANCE: MEETS OR EXCEEDS MB3513 PERFORMANCE SPECIFICATIONS
 CONTACT RATING: 3 AMPERE MAXIMUM
 INSULATION RESISTANCE: 5000 MEGOHMS MINIMUM @ 500 VDC
 CONTACT RESISTANCE: 8 MILLIOHMS MAX @ 2.5 AMPS

2. MATERIALS: INSULATOR: PPS PER MIL-M-24519 GST-40F, OR LCP (LIQUID CRYSTAL POLYMER)
 GLCP-30F COLOR: BLACK
 CONTACTS: BERYLLIUM COPPER PER ASTM B194, GOLD PLATED PER ASTM B488

1. MARKINGS: UMI, UMI P/N, DATE CODE & W/O NO. ON BAG OR TAG

NOTES: UNLESS OTHERWISE SPECIFIED

QUALITY SYMBOLS	UNLESS SPECIFIED, ALL DIMENSIONS IN INCHES	SCALE	DWG SIZE	THIRD ANGLE PROJECTION	REVISE ON CAD ONLY
HAZAR =	GENERAL TOLERANCES:	5:1	B		
CRITICAL C =	3 PLACE $\pm .005$	DRAWN BY & DATE			
SPC SPC =	2 PLACE $\pm .010$	PER 05-13-19			
	ANGULAR $\pm 2^\circ$	CHECKED BY & DATE			
		SEE ECN			
		APPROVED BY & DATE			
		SEE ECN			
		CAD FILENAME			
		SD-811081120.DWG			
		PART NO.			
		811081120			
		DRAWING NO.			
		SD-811081120			
		SHEET NO.			
		1 OF 1			
		PART REV			

10 9 8 7 6 5 4 3 2 1