



REVISIONS

PART REV.	DWG. ISSUE	DATE	ECN NO.	APPVD. BY	REL. BY
-	-	07/19/17	UMI6440	DW	DW



1	BLK
2	BRN
3	RED
4	ORG
5	YEL
6	GRN
7	BLU
8	VIO
9	GRY

3. PERFORMANCE SPECIFICATIONS:  
 CURRENT RATING: 3A MAX.  
 INSULATION RATING: 5,000 MΩ MIN.  
 DWV: 600 VAC.  
 TEMPERATURE RATING: 125°C.

2 MATERIALS:  
 SHELL: 6061-T6 ALUMINUM PER SAE-AMS-QQ-A200/8  
 CADMIUM PLATED PER SAE-AMS-QQ-P-416.  
 INSULATOR: PPS PER MIL-M-24519 GST-40F; COLOR: BLACK.  
 PIN CONTACTS: C17200 BERYLLIUM COPPER PER ASTM B194,  
 GOLD PLATED PER ASTM B488.

1 MARKING: UMI, DATE CODE, UMI P/N, AND UMI WORK ORDER NO..

NOTES: UNLESS OTHERWISE SPECIFIED

QUALITY SYMBOLS CRITICAL MAJOR NO SYMBOL = MINOR DIMENSION	<b>UNLESS SPECIFIED:</b> ALL DIMENSIONS IN INCHES GENERAL TOLERANCES: 3 PLACE ±.005 2 PLACE ±.01 ANGULAR ±2° ALL EXTERNAL SPECIFICATIONS REFERENCED ON THIS DRAWING SHALL BE THE LATEST REVISION IN EFFECT UMI-Mate CAGE CODE <b>58967</b>	SCALE 4:1 DWG SIZE B DRAWN BY & DATE DR 07/19/17 CHECKED BY & DATE SEE ECN APPROVED BY & DATE SEE ECN CAD FILENAME SD-834110070.SLDDRW	THIRD ANGLE PROJECTION TITLE MICRO-D PLUG, 9 PIN, 26 AWG TYPE 'E' WIRE LEADS, MR09P0-26E5-18.0 MATERIAL ENG PROJECT # - PART NO. 834110070 DRAWING NO. SD-834110070 SHEET NO. 1 OF 1 PART REV. -	REVISE ON CAD ONLY 
	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO ULTI-MATE INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.			