



2 MATERIALS:  
 SHELL: 6061-T6 OR 6061-T651 ALUMINUM PER SAE-AMS-00-A200/8,  
 CAD PLATED PER SAE-AMS-00-P-416  
 INSULATOR: PPS PER MIL-M-24519 GST-40F, COLOR: BLACK  
 PIN CONTACTS: C17200 BERYLLIUM COPPER PER ASTM B194,  
 GOLD PLATED PER ASTM B488  
 HARDWARE: STAINLESS STEEL 1AW MIL-DTL-8351.3, PASSIVATED  
 MARKING: "UMI", UMI DATE CODE, AND UMI PART NUMBER

1 NOTES: UNLESS OTHERWISE SPECIFIED.

QUALITY SYMBOLS	UNLESS SPECIFIED: ALL DIMENSIONS IN INCHES	SCALE 4 : 1	DWG SIZE B	THIRD ANGLE PROJECTION	REVISE ON CAD ONLY
MAJOR	GENERAL TOLERANCES: 3 PLACE ±.005 2 PLACE ±.01 ANGULAR ±2°	DRAWN BY & DATE DW 1-8-08	TITLE CONNECTOR ASSEMBLY, MR15P07-26M5-36.0		
CRITICAL	UMI-Mate CASE CODE <b>58967</b>	CHECKED BY & DATE	MATERIAL: CONNECTOR INCOMPONENT INC.		
SPC		APPROVED BY & DATE	PART NO. 834120397		
		CAD FILENAME SD-834120397.DGN	DRAWING NO. SD-834120397		
		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO ULTI-MATE INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.			
			SHEET NO. 1 OF 1		
			REV		